

HOST

iSAS 26-CKT
EXTERNAL
SFF-8088

GND	A1	-
RX0+	A2	-
RX0-	A3	-
GND	A4	-
RX1+	A5	-
RX1-	A6	-
GND	A7	-
RX2+	A8	-
RX2-	A9	-
GND	A10	-
RX3+	A11	-
RX3-	A12	-
GND	A13	-
GND	B1	-
TX0+	B2	-
TX0-	B3	-
GND	B4	-
TX1+	B5	-
TX1-	B6	-
GND	B7	-
TX2+	B8	-
TX2-	B9	-
GND	B10	-
TX3+	B11	-
TX3-	B12	-
GND	B13	-

TARGET

iSAS 36-CKT
4i INTERNAL
SFF-8087

B1	GND	-
B2	TX0+	-
B3	TX0-	-
B4	GND	-
B5	TX1+	-
B6	TX1-	-
B7	GND	-
B8	SB7	-
B9	SB3	-
B10	SB4	-
B11	SB5	-
B12	GND	-
B13	TX2+	-
B14	TX2-	-
B15	GND	-
B16	TX3+	-
B17	TX3-	-
A18	GND	-
A1	GND	-
A2	RX0+	-
A3	RX0-	-
A4	GND	-
A5	RX1+	-
A6	RX1-	-
A7	GND	-
A8	SB0	-
A9	SB1	-
A10	SB2	-
A11	SB6	-
A12	GND	-
A13	RX2+	-
A14	RX2-	-
A15	GND	-
A16	RX3+	-
A17	RX3-	-
A18	GND	-

PORT 0

PORT 1

PORT 2

PORT 3

P 1

P 2

NOT
CONN.

NOT
CONN.



Description: Cable, Host Based External 26-CKT Mini-SAS, TO Target Based Internal 36-CKT 4i Mini-SAS (SFF-8088 to SFF-8087)

Drawing No. iSAS-8873-U/xm	Sheet 2 of 2	Rev. A
--------------------------------------	-----------------	-----------

Rev	Date	Revision	ECO
A	11/17/06	Released	N/A